

R | Timber Grove II 30 mil PRODUCT SPECIFICATIONS



COLLECTION	Timber Grove II
STYLE NUMBER	I438V
CONSTRUCTION	Heavy Commercial Luxury Vinyl Tile
WEAR LAYER THICKNESS	30 mil / 0.03 inches (0.762 mm)
OVERALL THICKNESS	0.118 inches (3 mm)
EDGE PROFILE	Squared Edge
REFERENCE SPECIFICATION	ASTM F1700 Class III printed film vinyl plank Type B (embossed)
FINISH	ExoGuard+®
INSTALLATION TYPE	Dry Back
INSTALLATION	Glue Down
RECOMMENDED ADHESIVE	4200 (4 gal), 2200 (4 gal), 4252 (4 gal) or S150 SPRAY ADHS

Packaging

PLANK SIZE
PIECES /BOX
AREA /BOX
WEIGHT /BOX

US Units
 5.96 inches W x 48 inches L
 18
 35.76 sq ft
 33.3 lbs

Metric Units
 15.1 cm W x 121.9 cm L
 3.3 sq m
 15.1 kg

Performance Testing

STATIC LOAD / ASTM F970	Passes (Modified), *1500 lbs
RESIDUAL INDENTATION / ASTM F1914	Passes
RESISTANCE TO CHEMICALS / ASTM F925	Passes
RADIANT PANEL / ASTM E648	Passes, Class I
COEFFICIENT OF FRICTION (ASTM D2047, SLIP RESISTANCE)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranty


15 Year Commercial Limited.

Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient.


Please visit patcraft.com for the most current warranty information.

R | Timber Grove II 30 mil


Installation Methods



Brick



Herringbone



Stagger

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Environmental Specifications

EMBODIED CARBON (CRADLE TO GATE) 9.59 kg CO₂/m²

Materials

RECYCLED CONTENT Pre-consumer - 30%

Third Party Certifications

HEALTH PRODUCT DECLARATION (HPD) 1000 ppm Disclosure

ENVIRONMENTAL PRODUCT DECLARATION (EPD) 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

ENVIRONMENTAL GUARANTEE The products in this collection are In The Loop – they are fully recyclable through our re[TURN]® Reclamation Program. We will facilitate the pick-up and free return of a minimum of 100 SY of EcoWorx®, 500 SY of ReWorx™ products or 5,000 SF of Shaw-manufactured resilient products to be recycled. Participating in re[TURN]® lowers carbon emissions of these products by reducing virgin materials needed for making new products.

FLOORSCORE® Certified